

Development of Novel Materials for High-Performance Energy Storage Devices

A thesis presented for the award of the degree of

Doctor of Philosophy

from

University of Technology Sydney

By

Xiao Tang, B. Sc., M.Sc.

July, 2020

CERTIFICATE OF AUTHORSHIP

I, Xiao Tang, certify that the work presented in this thesis has not previously been submitted for a degree nor as a part for a degree.

I also certify that the thesis has been written by me. Any help that I have received in my research work and the preparation of the thesis itself has been acknowledged. In addition, I certify that all information sources and literature used are indicated in the thesis.

This research is supported by an Australian Government Research Training Program.

Xiao Tang

Production Note:

Signature removed prior to publication.

Sydney, Australia

11/07/2020

DEDICATION

To my beloved family. Thank you for giving a different meaning of life to me.

ACKNOWLEDGEMENTS

Before writing this thesis, I dedicated myself to list all the people who deserve my sincere acknowledgment. However, I may have dropped, unintentionally, some of them; I would like to ask for their forgiveness.

Firstly, I am grateful to my supervisor, Professor Guoxiu Wang, for his kind and continuous support and invaluable advice throughout my Ph.D. study. The helps and supports from Dr. Jane Yao are also appreciated.

Thanks to Dr. Dong Zhou, who taught me many skills he knows. Under his help, I am encouraged to think outside of the box, develop ideas and implement them. We discussed with each other and co-wrote the manuscript, which should be a great memory in my life.

Special thanks are given to my colleagues at UTS, Prof. Hao Liu, Dr. Dawei Su, Dr. Bing Sun, Dr. Xin Guo, Dr. Weizhai Bao, Dr. Anjon Kumar Mondal, Dr. Jinqiang Zhang, Dr. Yufei Zhao, Dr. Pan Xiong and Dr. Huajun Tian. Their kind collaboration and assistance were helpful. In addition, I would like to thank the administrative and technical support from Dr. Ronald Shimon, Dr. Linda Xiao, Herbert Yuan and Katie.

The financial support from UTS and China Scholarship Council (CSC) to help finish my Ph.D. study are highly appreciated.

Last but not the least, I would like to thank my parents, my girlfriend for supporting me spiritually throughout my Ph.D. study. Their accompanying always encourage me keep running in my career.

Xiao Tang

RESEARCH PUBLICATIONS

1. Xiao Tang, Dong Zhou*, Peng Li, Xin Guo, Bing Sun, Hao Liu, Kang Yan, Yury Gogotsi*, Guoxiu Wang*. MXene-based dendrite-free potassium metal batteries. **Adv. Mater.** 2020, 32 (4), 1906739.
2. Xiao Tang, Dong Zhou, Peng Li, Xin Guo, Chengyin Wang, Feiyu Kang, Baohua Li*, Guoxiu Wang*. High-performance quasi-solid-state MXene-based Li-I batteries. **ACS Cent. Sci.** 2019, 5 (2), 365-373.
3. Xiao Tang, Xin Guo, Wenjian Wu, Guoxiu Wang*. 2D metal carbides and nitrides (MXenes) as high-performance electrode materials for lithium-based batteries. **Adv. Energy Mater.** 2018, 8 (33), 1801897.
4. Weizhai Bao, Xiao Tang, Xin Guo, Sinho Choi, Chengyin Wang, Yury Gogotsi*, Guoxiu Wang*. Porous cryo-dried MXene for efficient capacitive deionization. **Joule** 2018, 2 (4), 778-787.
5. Dong Zhou, Xiao Tang, Xin Guo, Peng Li, Devaraj Shanmukaraj, Hao Liu, Xiaochun Gao, Yizhou Wang, Teofilo Rojo, Michel Armand, Guoxiu Wang*. Polyolefin-based Janus separator for rechargeable sodium batteries. **Angew. Chem. Int. Ed.** 2020, DOI: 10.1002/anie.202007008.
6. Dong Zhou, Anastasia Tkacheva, Xiao Tang, Bing Sun, Devaraj Shanmukaraj, Peng Li, Fan Zhang, Michel Armand, Guoxiu Wang*. Stable conversion chemistry-based lithium metal batteries enabled by hierarchical multifunctional polymer electrolytes with near-single ion conduction. **Angew. Chem. Int. Ed.** 2019, 58 (18), 6001-6006.

TABLE OF CONTENTS

Development of Novel Materials for High-Performance Energy Storage Devices	I
CERTIFICATE OF ORIGINAL AUTHORSHIP	1
DEDICATION	2
ACKNOWLEDGEMENTS	3
RESEARCH PUBLICATIONS	4
TABLE OF CONTENTS	5
LIST OF TABLES	8
LIST OF FIGURES	9
ABSTRACT	17
Chapter 1. Introduction	18
Chapter 2. Literature Review	22
2.1 Synthesis of the MXene materials	22
2.2 Structural characteristics and properties of MXenes	27
2.2.1 Structural properties and surface terminations.....	27
2.2.2 Physical properties	29
2.3 Application of MXenes for lithium-based batteries.....	31
2.3.1 Lithium-ion batteries.....	32
2.3.2 Lithium-sulfur batteries.....	47
2.3.3 Lithium metal anode	53
2.4 Application of MXenes for potassium-based batteries	56
Chapter 3 Experimental	61
3.1 Overview	61
3.2 Materials preparation	63
3.2.1 Melt diffusion and solution-adsorption methods	63
3.2.2 Chemical exfoliation	64
3.2.3 Drop-filtration method	64
3.2.4 Heat treatment	65
3.2.5 Infusion method	65
3.3 Materials characterization	65
3.3.1 X-ray Diffraction (XRD)	65
3.3.2 Raman Spectroscopy	66
3.3.3 <i>In situ</i> microscope	66

3.3.4 X-ray photoelectron spectroscopy (XPS).....	67
3.3.5 N ₂ sorption/desorption measurement	67
3.3.6 Thermogravimetric Analysis (TGA).....	68
3.3.7 Scanning Electron Microscopy (SEM)	68
3.3.8 Transmission Electron Microscopy (TEM)	68
3.4 Electrode preparation and battery assembly	69
3.4.1 Electrode preparation	69
3.4.2 Cell assembly	69
3.5 Electrochemical measurements.....	70
3.5.1 Galvanostatic charge-discharge	70
3.5.2 Cyclic voltammetry (CV).....	71
3.5.3 Electrochemical Impedance Spectroscopy (EIS)	71
Chapter 4 A High-performance Li-I battery enabled by a MXene wrapped carbon cloth-iodine electrode and a composite polymer electrolyte	72
4.1 Introduction.....	72
4.2 Experimental section.....	74
4.2.1 Synthesis of the Ti ₃ C ₂ T _x MXene.....	74
4.2.2 Preparation and characterization of the CC-I/MXene electrode	74
4.2.3 Preparation and characterization of the CPE	75
4.2.4 Assembly and testing of quasi-solid-state Li-I batteries	77
4.2.5 Theoretical calculations	78
4.3 Results and discussion	78
4.4 Conclusions.....	111
Chapter 5 High-performance potassium-sulfur batteries enabled by MXene-based dendrite-free potassium metal anodes.....	113
5.1 Introduction.....	113
5.2 Experimental section.....	115
5.2.1 Sample preparation	115
5.2.2 Characterization and electrochemical tests	116
5.3 Results and discussion	119
5.4 Conclusions.....	151
Chapter 6. High-performance Lithium-sulfur/ion batteries enabled by MXene interlayer.....	152
6.1 Introduction.....	152
6.2 Experimental section.....	154
6.2.1 Synthesis of sulfur@biocarbon (S@C).....	154

6.2.2 Synthesis of MXene and MXene interlayer	154
6.2.3 Structure and morphology characterizations.....	155
6.2.4 Electrochemical characterizations.....	155
6.3 Results and discussion	156
6.4 Conclusions.....	165
Chapter 7 Conclusions and future perspective.....	166
APPENDIX: NOMENCLATURE.....	169
REFERENCES	172

LIST OF TABLES

Table 2.1. Summary of MXenes produced by wet etching methods and related exfoliation parameters. .	26
Table 2.2. Summary of electrochemical performances of MXene and MXene-based composites for lithium-ion batteries.....	46
Table 2.3. Summary of electrochemical performances of MXene and MXene-based composites in lithium-sulfur batteries.....	55
Table 2.4. Summary of electrochemical performances of MXene and MXene-based composites for potassium-based batteries.	59
Table 3.1. Chemicals details in the research project.	62
Table 4.1. The values of VTF fitting parameters in Figure 4.11a.	93
Table 4.2. EIS simulation results from Figure 4.19.	105
Table 4.3. The power densities and energy densities of the Li CPE CC-I/MXene cell.....	108
Table 5.1. Summary of the Coulombic efficiencies and cycling performances of K metal deposition on current collectors/ scaffolds.	137
Table 5.2. The EIS results obtained from Figure 5.31.	150

LIST OF FIGURES

Figure 2.1. **a)** Schematic for the exfoliation process of MAX phases and the formation of MXenes. Reproduced with permission.¹³ Copyright 2014, American Chemical Society. **b)** Schematic for the exfoliation of Ti_3SiC_2 and the formation of Ti_3C_2 MXene using an etching solution consisting of HF and an oxidant. Reproduced with permission.⁴⁶ Copyright 2018, Wiley-VCH. **c)** Schematic for the exfoliation of the MAX phase by alkali (NaOH) treatment. Reproduced with permission.⁴⁷ Copyright 2018, Wiley-VCH.

..... 24

Figure 2.2. Optimized geometries of bare Ti_3C_2 MXene and its functionalized derivatives with different configurations. Side views of **a)** bare Ti_3C_2 ; **b)** $\text{Ti}_3\text{C}_2\text{F}_2$: i) I- $\text{Ti}_3\text{C}_2\text{F}_2$, ii) II- $\text{Ti}_3\text{C}_2\text{F}_2$, and iii) III- $\text{Ti}_3\text{C}_2\text{F}_2$; **c)** $\text{Ti}_3\text{C}_2(\text{OH})_2$: i) I- $\text{Ti}_3\text{C}_2(\text{OH})_2$, ii) II- $\text{Ti}_3\text{C}_2(\text{OH})_2$, and iii) III- $\text{Ti}_3\text{C}_2(\text{OH})_2$; top views of **d)** $\text{Ti}_3\text{C}_2\text{F}_2$: i) I- $\text{Ti}_3\text{C}_2\text{F}_2$ and ii) II- $\text{Ti}_3\text{C}_2\text{F}_2$. Because configuration III is a mixture of configurations I and II, the top view of configuration III is not shown.⁶⁴ Reproduced with permission. Copyright 2012, American Chemical Society. Total and partial density of states of **e)** Ti_2CT_2 and **f)** Ti_2NT_2 MXene, and related MAX phases calculated using the HSE06 functional.⁷² Reproduced with permission. Copyright 2013, American Physical Society. 30

Figure 2.3. **a)** Schematic illustration for the preparation of intercalated MXene by the intercalation of urea molecules. **b)** XRD patterns of surface-functionalized Ti_3C_2 : i) before treatment, ii) after intercalation treatment followed by washing with DMF, and iii) after intercalation treatment, washing with ethanol and drying under different conditions. **c)** Magnified view of c in the $5\text{--}12^\circ 2\theta$ range showing the (0002) peaks. SEM images of Ti_3C_2 **d)** before and **e)** after intercalation. **f)** XRD patterns of i) Ti_3AlC_2 , ii) exfoliated Ti_3C_2 , iii) DMSO intercalated Ti_3C_2 and iv) delaminated Ti_3C_2 . **g)** Comparison of the performances of exfoliated and delaminated functionalized Ti_3C_2 in lithium-ion batteries. The inset is an SEM image of the delaminated Ti_3C_2 film. Scale bars: 200 nm in d), e).⁴² Reproduced with permission. Copyright 2013, Macmillan Publishers Ltd. 35

Figure 2.4. **a)** Schematic illustration for the preparation of $\text{M}'_2\text{M}''\text{C}_2/\text{M}'_2\text{M}''_2\text{C}_3$ MXene structures. **b)** Transformation mechanism of $\text{Mo}_2\text{TiAlC}_2$ to $\text{Mo}_2\text{TiC}_2\text{T}_x$. **c)** Total energy diagram of the Mo_2TiC_2 monolayer as a function of Ti concentration in the middle layer. **d)** SEM and TEM images of the $\text{Mo}_2\text{TiC}_2\text{T}_x$ MXene and $\text{Mo}_2\text{TiAlC}_2$ MAX phases. **e)** Delaminated $\text{Mo}_2\text{TiC}_2\text{T}_x$ MXene: i) schematic illustration for the preparation of delaminated $\text{Mo}_2\text{TiC}_2\text{T}_x$; ii) Tyndall effect on $\text{Mo}_2\text{TiC}_2\text{T}_x$ aqueous solution; iii) low-resolution and iv) high-resolution SEM images of $\text{Mo}_2\text{TiC}_2\text{T}_x$ “paper”. **f)** Cycling performances of $\text{Mo}_2\text{TiC}_2\text{T}_x$ paper at C/10 and 1 C rates. (green circles: Ti atoms, red circles: Mo atoms, black circles: C atoms, blue circles: Al atoms).¹⁴ Reproduced with permission. Copyright 2015, American Chemical Society.

..... 37

Figure 2.5. Two examples of the MXene architectures construction. **a)** Illustration for the preparation of vertical alignment by mechanical shearing of a discotic lamellar liquid-crystal phase of $\text{Ti}_3\text{C}_2\text{T}_x$; **b)** Side view and top view of SEM images of the MXLLC; **c)** Schematic of ion transport in the vertically aligned MXene film. Reproduced with permission.⁹⁶ Copyright 2018, Nature publishing group. **d)** Schematic showing the fabrication of hollow MXene spheres and 3D macroporous MXene frameworks; **e)** Cross-sectional SEM image and digital image (inset) of a 3D macroporous film. Reproduced with permission.⁹⁷ Copyright 2017, Wiley-VCH. 38

Figure 2.6. **a)** Schematic illustration for the preparation of MXene/CNF hybrid particles, SEM images of **b)** the as-etched $\text{Ti}_3\text{C}_2\text{T}_x$ and **c)** the $\text{Ti}_3\text{C}_2\text{T}_x/\text{CNF}$ composite. **d)** Cycling stability of the $\text{Ti}_3\text{C}_2\text{T}_x$ sample at 1 C and the $\text{Ti}_3\text{C}_2\text{T}_x/\text{CNF}$ sample at 1 C and 100 C.¹⁰⁴ Reproduced with permission. Copyright 2015, The Royal Society of Chemistry. **e)** Schematic illustration for the preparation of delaminated Nb_2CT_x . **f)** TEM image of delaminated Nb_2CT_x flakes. Cross-sectional SEM images of **g)** bare Nb_2CT_x and **h)** $\text{Nb}_2\text{CT}_x/\text{CNT}$ composite paper.¹⁰⁵ Reproduced with permission. Copyright 2015, WILEY-VCH. 40

Figure 2.7. **a)** SEM image of PVP-Sn(IV)@ Ti_3C_2 nanocomposites; **b)** Rate performance of the PVP-Sn(IV)@ Ti_3C_2 nanocomposite; **c)** Cycling performances of different electrodes.¹⁰⁶ Reproduced with permission. Copyright 2016, American Chemical Society. **d)** TEM image of the MXene/10Ag composite; **e)** Rate performances of an MXene/Ag electrode and an MXene electrode; **f)** Cycling performances of an MXene/10Ag electrode and an MXene electrode.¹⁰⁸ Reproduced with permission. Copyright 2016, American Chemical Society. 41

Figure 2.8. **a)** Schematic illustration of the structure of composites before and after oxidation. **b)** SEM image of the $\text{Nb}_2\text{O}_5@\text{Nb}_4\text{C}_3\text{T}_x$ composite. **c)** Discharge profiles of the $\text{Nb}_2\text{O}_5@\text{Nb}_4\text{C}_3\text{T}_x$ and $\text{Nb}_4\text{C}_3\text{T}_x$ electrodes collected at 50 mA g^{-1} . **d)** SEM image of the $\text{TiO}_2@\text{Ti}_3\text{C}_2\text{T}_x$ composite. The inset shows a higher magnification SEM image. **e)** Discharge profiles of the $\text{TiO}_2@\text{Ti}_3\text{C}_2\text{T}_x$ and $\text{Ti}_3\text{C}_2\text{T}_x$ electrodes collected at 50 mA g^{-1} .¹⁰⁹ Reproduced with permission. Copyright 2016, WILEY-VCH. **f)** Schematic illustration for the in situ growth procedures of a $\text{Ti}_3\text{C}_2\text{T}_x/\text{NiCo}_2\text{O}_4$ hybrid film.¹¹¹ Reproduced with permission. Copyright 2016, Elsevier. **g)** Schematic illustration of different methods applied to deposit SnO_2 onto MXene.¹¹² Reproduced with permission. Copyright 2017, Elsevier. 43

Figure 2.9. **a)** Schematic illustration for the preparation of $\text{MoS}_2/\text{MXene}$ hybrids. SEM image **b)** and TEM image **c)** of $\text{MoS}_2/\text{Mo}_2\text{TiC}_2\text{T}_x-500$. **d)** Galvanostatic charge/discharge profiles of $\text{MoS}_2/\text{Mo}_2\text{TiC}_2\text{T}_x-500$ at 100 mA g^{-1} . Adsorption sites of lithium ions on **(e)** MoS_2 and **(f)** $\text{MoS}_2/\text{Mo}_2\text{TiC}_2\text{O}_2$. **(g)** Binding energies of lithium ions on the surface of MoS_2 and $\text{MoS}_2/\text{Mo}_2\text{TiC}_2\text{O}_2$. The most stable adsorption configurations and binding energies of Li_2S on **(h)** MoS_2 and **(i)** $\text{Mo}_2\text{TiC}_2\text{O}_2$.¹¹⁴ Reproduced with permission. Copyright 2017, WILEY-VCH. 45

Figure 2.10. **a)** Schematic illustration for the replacement mechanism of the Ti-OH bond by a S-Ti-C bond via heat treatment or direct contact with polysulfides. XPS analysis of the Ti_2C sheets and S/ Ti_2C composite. **b)** Ti 2p spectra of the i) Ti_2C sheets and ii) 70S/ Ti_2C composite, iii) $\text{Li}_2\text{S}_4\text{-Ti}_2\text{C}$ and iv) 70S/ Ti_2C electrode discharged to 1.8 V at C/20. **c)** S 2p spectra of i) elemental sulfur, ii) 70S/ Ti_2C composite, and iii) 70S/ Ti_2C electrode discharged to 1.8 V at C/20.⁸⁹ Reproduced with permission. Copyright 2015, WILEY-VCH. **d)** Schematic illustration for the two-step interaction between polysulfides and MXene with -OH terminations. **e)** Theoretical calculations for the interaction between polysulfide Li_2S_4 and Ti_3C_2 MXene: i) $\text{Ti}_3\text{C}_2(\text{OH})_2$, ii) $\text{Ti}_3\text{C}_2(\text{OH})_2$ with one hydroxyl vacancy, and iii) fully exposed Ti_3C_2 , along with iv) the differences in the binding energies of polysulfide molecules (e.g., Li_2S , Li_2S_2 , and Li_2S_4) to the different matrices.¹²⁴ Reproduced with permission. Copyright 2017, WILEY-VCH. 50

Figure 2.11. **a)** Schematic illustration for the synthesis procedure of crumpled N- $\text{Ti}_3\text{C}_2\text{T}_x/\text{S}$ composites. **b)** Morphologies of crumpled N- $\text{Ti}_3\text{C}_2\text{T}_x$ nanosheets and crumpled N- $\text{Ti}_3\text{C}_2\text{T}_x/\text{S}$ composites: i, ii) FE-SEM image of crumpled N- $\text{Ti}_3\text{C}_2\text{T}_x$ nanosheets. iii) HRTEM image of crumpled N- $\text{Ti}_3\text{C}_2\text{T}_x$ nanosheets. iv, v) FE-SEM image of crumpled N- $\text{Ti}_3\text{C}_2\text{T}_x/\text{S}$ composites. vi) HRTEM image of crumpled N- $\text{Ti}_3\text{C}_2\text{T}_x/\text{S}$ composites. Scale bars: $2 \mu\text{m}$ (i, iv), 200 nm (ii, v) and 100 nm (iii, vi). **c)** Ultraviolet/visible adsorption spectra and digital images (inset) of a Li_2S_6 solution before and after adding crumpled N- $\text{Ti}_3\text{C}_2\text{T}_x$ and mixed- $\text{Ti}_3\text{C}_2\text{T}_x$.¹²⁹ Reproduced with permission. Copyright 2018, WILEY-VCH. 51

Figure 2.12. **a)** Schematic illustration of the configurations of lithium-sulfur batteries using a porous PP separator and an MXene-coated PP separator. **b)** Electrochemical characterizations of two lithium-sulfur batteries with PP and MPP separators: The initial voltage profiles of cells with i) a PP separator and ii) an MPP separator at 0.2, 0.5, and 1 C. iii) Comparative analysis of the potential difference of two cells between the charge and discharge plateaus at 0.2, 0.5, and 1 C. iv) Rate performances of above two cells.¹³¹ Reproduced with permission. Copyright 2016, American Chemical Society. **c)** Configurations of S₈, Li₂S, Li₂S₄, Li₂S₆ and Li₂S₈ on Ti₃C₂ MXene. **d)** Binding energies of Li₂S, Li₂S₄, Li₂S₆ and Li₂S₈ on graphene, Ti₃C₂(OH)₂ MXene, and Ti₃C₂ MXene. Digital images of the diffusion of polysulfides: H-type cells with **e)** a glass fiber separator and **f)** a Ti₃C₂ MXene-covered glass fiber composite separator.¹³² Reproduced with permission. Copyright 2016, The Royal Society of Chemistry. 53

Figure 2.13. Fabrication of flexible lamellar-structured Ti₃C₂ MXene-Li films. **a)** Schematic illustration for the preparation procedures of Ti₃C₂ MXene-Li films. **b)** Top and **c)** cross-sectional SEM images of a Ti₃C₂ MXene-Li hybrid film with a layered structure. **d)** Cycle performances of symmetric cells of Ti₃C₂-Li, Graphene-Li, BN-Li and bare Li at a constant current density of 1.0 mA cm⁻². **e)** In situ TEM images of growing lithium into the Ti₃C₂ MXene-Li films. **f)** In situ TEM images of growing lithium dendrites outside of the Ti₃C₂ MXene-Li films.¹³³ Reproduced with permission. Copyright 2017, Elsevier. 55

Figure 3.1. The diagram that demonstrates the procedures of the experiments. 61

Figure 3.2. the schematic illustration of as-assembled cell for in situ microscope. 67

Figure 4.1. Schematic illustration of the preparation of MXene wrapped carbon cloth-iodine cathodes and composite polymer electrolyte. 80

Figure 4.2. Characterizations of the delaminated MXene sheets. (a) FE-SEM image of the delaminated MXene sheets. (b-e) EDS elemental mapping of elemental Ti, C, O and F of the delaminated MXene sheets. (f) XRD pattern and (g) Raman spectrum of the delaminated MXene sheets. 80

Figure 4.3. (a) TGA curves of the pure iodine, CC-I, and CC-I/MXene samples under N₂ flow from room temperature to 600 °C. (b) Thermogravimetric analysis curves of the CC-I/MXene electrode with different areal mass loading of iodine. 81

Figure 4.4. The initial discharge/charge curves at 0.5 C of (a) pristine Li|1 M LiTFSI in DOL: DME (LE)|CC-I cathode cell; (b) cycled Li|LE|CC-I cathode cell, the cycled Li anode was obtained from a CC-I cathode|LE with 1 wt% LiNO₃ additive|pristine Li cell after 5 cycles at 0.5 C; (c) pristine Li|LE with 2 wt% LiNO₃ additive|CC-I cathode and pristine Li|suspension of 2 wt% NaNO₃ in LE additive|CC-I cathode cells, and (d) pristine Li|the filtrate of a suspension of 2 wt% NaNO₃ in LE|CC-I cathode cell. 83

Figure 4.5. Optical images of (a) the precursor solution of CPE, and (b-d) GPE and CPE. (e) GPE and (f) CPE under the pressure of a 100 g weight. 84

Figure 4.6. Characterizations of the carbon cloth-iodine electrode. (a-b) FE-SEM images of the CC-I electrode. (c-e) EDS Elemental mapping of the CC-I electrode. The elemental mapping analysis of the CC-I sample in Figure 4.6c-e demonstrates that I and C elements are evenly distributed, confirming the successful loading of iodine into the pores of carbon fibres. 86

Figure 4.7. Characterizations of CC-I/MXene electrodes. (a) FE-SEM images and (b) EDS mappings of elemental Ti, C and I on a CC-I/MXene electrode; High resolution XPS spectra of (c) Ti 2p and (d) I 3d in a CC-I/MXene electrode; (e) UV-vis spectra and corresponding digital images of 10 mM LiI₃ solution before and after loading MXene sheets; (f) The initial discharge/charge curves of Li|LE|CC-I and a Li|LE|CC-I/MXene cells at 0.5C. 87

- Figure 4.8.** Characterizations of the MXene wrapped carbon cloth-iodine electrode. (a-b) FE-SEM images of CC-I/MXene electrode. (c) XRD patterns of CC-I and CC-I/MXene electrodes. The MXene (002) peak at around 6° peak indicates the successful preparation of the CC-I/MXene electrode without any compositional change. (d) Raman spectrum of CC-I/MXene electrode. The peaks located at ~ 200 , ~ 378 , and $\sim 607\text{ cm}^{-1}$ can be assigned to specific $\text{Ti}_3\text{C}_2\text{Tx}$ MXene bands while two peaks at ~ 1355 and $\sim 1600\text{ cm}^{-1}$ can be ascribed to the D band and G band of carbon cloth, respectively.¹⁶⁷ 88
- Figure 4.9.** (a) C 1s and (b) O 1s XPS spectra of the as-prepared CC-I/MXene electrode. The C 1s XPS spectrum of CC-I/MXene electrode in Figure 4.9a can be deconvoluted into five peaks at 281.7, 284.8, 286.3, 288.3 and 289.2 eV. The peak at 281.7 eV can be assigned to the C-Ti bond. The peaks at 284.8 eV and 286.3 eV relate to C-C and C-O, respectively. The other two peaks appearing at 288.3 and 289.2 eV can be indexed to the signals of C=O and O-C=O/C-F, respectively.¹²⁴ 89
- Figure 4.10.** FTIR spectra of PETEA monomer and the PETEA-based polymer matrix of CPE..... 90
- Figure 4.11.** Characterizations of the CPE. (a) The ionic conductivities of 1 M LiTFSI in DOL: DME (1: 1, v/ v) LE, LE suspended with NaNO_3 and CPE as a function of temperature. The plots represent the experimental data meanwhile the solid lines represent VTF fitting results. (b) The chronoamperometry profile of a symmetric Li|CPE|Li cell under a polarization voltage of 10 mV. The corresponding EISs before and after the polarization are shown in inset. (c) Galvanostatic cycling curves of Li|Li symmetrical cells using LE or CPE at a current density of 0.5 mA cm^{-2} with cutoff capacity of 1.5 mAh cm^{-2} ; (d) Weight loss of LE and CPE along with aging time at 25°C . (e) Visual observation of iodine dissolution/diffusion in LE and CPE with different aging times. 92
- Figure 4.12.** The chronoamperometry profile of symmetric Li|LE|Li cell under a polarization voltage of 10 mV. The corresponding EISs before and after the polarization are shown in inset. 93
- Figure 4.13.** The potential change of Li|LE|CC-I/MXene, Li|LE+ NaNO_3 |CC-I/MXene, and Li|CPE|CC-I/MXene cells over standing time. 95
- Figure 4.14.** Electrochemical characterizations of Li-I cells. (a) The initial charge/discharge curves and (b) cycling performances of Li|LE|CC-I/MXene and Li|CPE|CC-I/MXene cells at 0.5 C, and (c) CV curves at 0.1 mV s^{-1} . The morphologies and corresponding EDS mappings of iodine (shown in insets) of Li anodes obtained from the (d) Li|LE|CC-I/MXene and (e) Li|CPE|CC-I/MXene cells after 50 cycles at 0.5 C. (f) The Rate performances of above two Li-I cells; (g) Ragone plot of the as-assembled Li|CPE|CC-I/MXene battery compared with previously reported Li-I batteries^{148, 155, 157} (hollow symbols) and representative Li-ion batteries¹⁷² (solid symbols). (h) Digital images of an as-prepared CC-I/MXene cathode (upper right), and a red LED powered by a flexible Li|CPE|CC-I/MXene cell under flat–bent–flat states. 96
- Figure 4.15.** Charge/discharge curves of (a) Li|LE|carbon cloth and (b) Li|LE|MXene wrapped carbon cloth cells at different current densities. 97
- Figure 4.16.** Electrochemical characterizations of the Li|LE+ NaNO_3 |CC-I/MXene cell. (a) The initial charge/discharge curves and (b) cycling performance at 0.5 C, and (c) CV curves at 0.1 mV s^{-1} . (d) The Rate performance of the Li|LE+ NaNO_3 |CC-I/MXene cell; (e) The morphology and corresponding EDS mapping of iodine (shown in insets) of Li anodes obtained from the Li|LE+ NaNO_3 |CC-I/MXene cell after 50 cycles at 0.5 C. 98
- Figure 4.17.** (a) The initial five CV curves of Li|CPE|CC-I/MXene cell at 0.1 mV s^{-1} ; (b) CV curves of Li|CPE|CC-I/MXene cell at different scan rates. (c) Plot of $\log(\text{peak current})$ as function of $\log(\text{scan rate})$ obtained from Figure S14b. (d) The calculated non-capacitive behaviour and total current in Li|CPE|CC-I/MXene cell at 0.5 mV s^{-1} 101

Figure 4.18. Ex situ Raman spectrum at various charge/discharge states and the corresponding charge/discharge curves at 0.2 C of the (a) Li CPE CC-I/MXene and (b) Li LE CC-I/MXene cells.....	102
Figure 4.19. EISs of Li CPE CC-I/MXene, Li LE+NaNO ₃ CC-I/MXene, and Li LE CC-I/MXene cells. (a) after the 1 st cycle and (b) after the 50 th cycle at 0.5 C, measured in the half charged state; (c) Experimental and simulation EIS curves of the Li LE CC-I/MXene cell using an equivalent circuit shown in inset. ¹⁸⁰	104
Figure 4.20. Digital images of Li anodes obtained from (a) Li LE CC-I/MXene, (b) Li LE+NaNO ₃ CC-I/MXene and (c) Li CPE CC-I/MXene cells after 50 cycles at 0.5 C.	105
Figure 4.21. Charge/discharge curves of (a) Li CPE CC-I/MXene, (b) Li LE+NaNO ₃ CC-I/MXene, and (c) Li LE CC-I/MXene cells at different current densities.	107
Figure 4.22. Cycling performances of the Li CPE CC-I/MXene cell at 0.5 C with different areal mass loading of iodine in the cathode.	108
Figure 4.23. Theoretical calculations. Molecular models and calculated binding energies of LiI ₃ with (a) DOL; (b) DME; (c) PETEA monomer and (d) Ti ₃ C ₂ F ₂ ; (e) Ti ₃ C ₂ O ₂ ; (f) Ti ₃ C ₂ (OH) ₂ as Ti ₃ C ₂ T _x MXenes. g) Side view and h) top view of the difference in charge density for the optimized structure of LiI ₃ adsorbed on Ti ₃ C ₂ (OH) ₂ MXene. Yellow and blue color indicate the charge depletion and accumulation, respectively.	110
Figure 4.24. a) Side view and b) top view of the difference in charge density for the optimized structure of LiI ₃ adsorbed on Ti ₃ C ₂ F ₂ MXene. c) Side view and d) top view of the difference in charge density for the optimized structure of LiI ₃ adsorbed on Ti ₃ C ₂ O ₂ MXene. Yellow and blue color indicate the charge depletion and accumulation, respectively.	111
Figure 5.1. Schematic illustration and morphological characterizations. (a) Schematic illustration for the preparation of the DN-MXene/CNT scaffold and K@DN-MXene/CNT metallic anodes; (b) High-magnification HAADF-STEM images of DN-MXene sheets; (c) The simulated and (d) corresponding experimental atomic-resolution HAADF-STEM images of the DN-MXene sheets; Ti: yellow atoms, C: grey atoms, N: blue atoms, Ti vacancy: circles, surface groups: red atoms. (e) Top-view and cross-sectional (shown in inset) SEM images of the DN-MXene/CNT scaffold; (f) Top-view SEM image of a K@DN-MXene/CNT metallic anode; Optical images of DN-MXene/CNT free-standing scaffold before (left) and after (right) the infusion process are shown in inset.	119
Figure 5.2 The SEM image of the as-prepared Ti _{3-x} CNT _y MXene sheets. Scale bar is 10 μm.....	121
Figure 5.3 High resolution XPS spectra of a Ti 2p, b C 1s, and c N 1s of the DN-MXene/CNT scaffold.	122
Figure 5.4 AFM image and corresponding height profiles of the as-obtained Ti _{3-x} CNT _y MXene sheet.	122
Figure 5.5. The cross-sectional morphologies of the DN-MXene/CNT scaffold.	124
Figure 5.6. The (a) top-view and (b) cross-sectional morphologies of the CNT scaffold.	125
Figure 5.7. (a) XRD and (b) Raman spectra of the DN-MXene/CNT scaffold. (Supplementary Note 2.)	125
Figure 5.8. The optical images showing that K metal melting and diffusion on the DN-MXene/CNT scaffold.....	126
Figure 5.9. Density functional theory calculations and corresponding experimental characterizations. The deformation charge density of K atoms absorbed on (a) Cu, (b) Al, (c) CNT, (d) Ti _{3-x} CN(OH) ₂ , (e) Ti _{3-x} CNO ₂ and (f) Ti _{3-x} CNF ₂ ; (g) The calculated binding energies of K atoms with different scaffolds or current	

collectors; (h) The voltage profiles of K nucleation on MXene/CNT scaffold, CNT scaffold, Cu foil, and Al foil at a current density of 0.05 mA cm^{-2} .	127
Figure 5.10. The deformation charge density of K atoms absorbed on (a) Cu, (b) Al, (c) CNT, and (d) $\text{Ti}_{3-x}\text{CN}(\text{OH})_2$, (e) $\text{Ti}_{3-x}\text{CNO}_2$, (f) $\text{Ti}_{3-x}\text{CNF}_2$.	128
Figure 5.11. (a) The discharge profile of the DN-MXene/CNT scaffold at a current density of 0.05 mA cm^{-2} ; (b) The corresponding XRD patterns of the DN-MXene/CNT scaffold before and after discharge.	128
Figure 5.12. The deformation charge density of K atoms absorbed on the defect-free (a) $\text{Ti}_3\text{CN}(\text{OH})_2$, (b) Ti_3CNO_2 , (c) Ti_3CNF_2 MXenes.	129
Figure 5.13. The deformation charge density of K atoms absorbed on the N-free defect-free (a) $\text{Ti}_3\text{C}_2(\text{OH})_2$, (b) $\text{Ti}_3\text{C}_2\text{O}_2$, (c) $\text{Ti}_3\text{C}_2\text{F}_2$ MXenes.	129
Figure 5.14. (a) The overpotentials of N-free MXene/CNT scaffold and DN-MXene/CNT scaffold at a current density of 0.05 mA cm^{-2} . (b) The Coulombic efficiency of K plating/stripping on the N-free $\text{Ti}_3\text{C}_2\text{T}_x$ MXene/CNT scaffold at a current density of 0.5 mA cm^{-2} in the KPF_6 -based electrolyte.	130
Figure 5.15. Electrochemical performances of DN-MXene/CNT scaffold. (a) The Coulombic efficiencies of K plating/stripping on different scaffolds and current collectors at a current density of 0.5 mA cm^{-2} in KPF_6 -based electrolyte; (b) The corresponding voltage profiles of K plating/stripping on different scaffolds and current collectors at the 20 th cycle in KPF_6 -based electrolyte; (c-d) Top-view SEM images of K deposition onto (c) Cu and (d) DN-MXene/CNT at a current density of 0.5 mA cm^{-2} with a plating capacity of 5 mAh cm^{-2} in KPF_6 -based electrolyte; (e) The Coulombic efficiencies of K plating/stripping on different scaffolds and current collectors at a current density of 0.5 mA cm^{-2} in KFSI-based electrolyte.	132
Figure 5.16. Top-view SEM images of K deposition onto (a) Al and (b) CNT at a current density of 0.5 mA cm^{-2} with a plating capacity of 5 mAh cm^{-2} in KPF_6 -based electrolyte.	134
Figure 5.17. The cross-sectional morphologies of K deposited on (a) Cu, (b) Al, (c) CNT, and (d) DN-MXene/CNT at a current density of 0.5 mA cm^{-2} with a plating capacity of 5 mAh cm^{-2} in KPF_6 -based electrolyte.	135
Figure 5.18. The elemental mapping images of Ti, C, N, and K taken from the cross-sectional area of the K deposited DN-MXene/CNT scaffold.	135
Figure 5.19. SEM images of the DN-MXene/CNT scaffold after plating K in KPF_6 -based electrolyte with capacities of (a) 0 mAh cm^{-2} , (b) 1 mAh cm^{-2} , (c) 2.5 mAh cm^{-2} , (d) 5 mAh cm^{-2} .	135
Figure 5.20. The voltage profiles of K plating/stripping on different scaffolds and current collectors at the 20 th cycle in KFSI-based electrolyte.	136
Figure 5.21. In situ XRD analysis of the K deposition on (a) Cu and (b) DN-MXene/CNT scaffold.	138
Figure 5.22. Mechanism investigation in KPF_6 -based electrolyte. Contour plots of in situ XRD patterns for the K deposited on the (a) Cu and (b) DN-MXene/CNT scaffold. The corresponding electroplating curves are shown on the left; the high-intensity peak at around 26.8° is assigned to the Be window. (c) In situ optical microscopy visualization of K deposited on the Cu foil scaffold (left panel) and DN-MXene/CNT (right panel) at a current density of 2 mA cm^{-2} .	139
Figure 5.23. The voltage profiles of K plating on Cu foil and DN-MXene/CNT scaffold at a constant current density of 2 mA cm^{-2} , blue arrows indicate the characteristic Sand's time when dendrite formation starts, as denoted by the voltage divergence.	139

Figure 5.24. The voltage profiles of stripping K metal in K@DN-MXene/CNT Cu and bare K Cu cells at a current density of 0.05 mA cm ⁻² in KPF ₆ electrolyte. The capacities were calculated based on the mass of the anode.	141
Figure 5.25. The electrochemical performances of symmetric cells in KPF ₆ -based electrolyte. (a) Voltage profiles of symmetric cells with K@DN-MXene/CNT, K@CNT, or bare K metal anodes at a current density of 0.5 mA cm ⁻² , and (b) Corresponding voltage hysteresis of the as-assembled symmetric cells during cycling; (c) Rate performances of three symmetric cells at different current densities; (d) The EIS spectra of three symmetric cells after 10h charge-10h discharge cycles at 0.5 mA cm ⁻² ; (e) Schematic illustration of plating/stripping of K metal on CNT scaffold (upper panels) and DN-MXene/CNT scaffold (lower panels).	142
Figure 5.26. The enlarged voltage profiles of K@DN-MXene/CNT K@DN-MXene/CNT and K@CNT K@CNT symmetric cells at a current density of 0.5 mA cm ⁻²	143
Figure 5.27. The cycling stability of K@DN-MXene/CNT K@DN-MXene/CNT symmetric cell at a current density of 0.5 mA cm ⁻² in the KFSI-based electrolyte.	143
Figure 5.28. Electrochemical performances of K@DN-MXene/CNT SPAN and bare K SPAN K-S batteries. (a) Digital images (shown in inset) and the corresponding UV-vis spectra of liquid electrolytes in optically transparent devices assembled with K@DN-MXene/CNT anode (or bare K foil) and SPAN powder immersed in liquid electrolytes; (b) Rate performances of K@DN-MXene/CNT SPAN and bare K SPAN K-S batteries; (c) Cycling performances of K@DN-MXene/CNT SPAN and bare K SPAN K-S batteries at a current density of 0.5 C, and (d) Corresponding discharging-charging profiles at the 2 nd cycle and 200 th cycle; (e) The EIS spectra of two K-S batteries after different cycles at 0.5 C.	145
Figure 5.29. The voltage profiles of (a) K@DN-MXene/CNT SPAN cell and (b) bare K SPAN cell at different current densities.	147
Figure 5.30. (a) The initial voltage profiles of K@DN-MXene/CNT SPAN and bare K SPAN cells at a current density of 0.5 C. (b) The CV curves of K@DN-MXene/CNT SPAN and bare K SPAN cells at a scan rate of 0.1 mV s ⁻¹	148
Figure 5.31. (a) The EIS spectra of the K@DN-MXene/CNT SPAN and bare K SPAN cells after 1 cycle and 50 cycles. (b) Experimental and simulation EIS curves of the K@DN-MXene/CNT SPAN cell after 1 cycle; Inset is the corresponding equivalent circuit diagram.	149
Figure 5.32. The top-view morphology of the bare K anode disassembled from a K-S battery after 50 cycles. The elemental mapping and content of sulfur are shown in inset.	150
Figure 5.33. The schematic illustration of (a) K@DN-MXene/CNT and (b) bare K anodes recovered from the cycled K-S batteries.	150
Figure 6.1. Characterizations of biocarbon and S@C composites. a) the SEM image of the biocarbon materials; b) the SEM image of the S@C anode materials; c) the EDS elemental mapping of the C and S in S@C anode materials.	157
Figure 6.2. The TGA curves of the S@C anode materials.	157
Figure 6.3. a) The stable voltage windows of diluted and concentrated electrolytes on stainless steel mesh electrode. Linear sweep voltammetry was carried out at a scan rate of 10 mV s ⁻¹ ; b) The optical images of polysulfides dissolution/diffusion in diluted and concentrated electrolytes.	159
Figure 6.4. The Cyclic voltammetry (CV) curves of a) S@C anode and b) LiMn ₂ O ₄ cathode in concentrated electrolyte at a scan rate of 0.2 mV s ⁻¹	160

Figure 6.5. a) The SEM image of the commercial LiMn_2O_4 cathode materials; b) the XRD pattern of the LiMn_2O_4 cathode materials.	160
Figure 6.6. a) The top-view SEM image of the as-prepared MXene paper, the inset image shows the optical image of the free-standing MXene paper; b) The XRD pattern of the as-prepared MXene paper; high resolution XPS spectrum of c) Ti 2p and d) C 1s in the MXene paper.	161
Figure 6.7. a) The schematic illustration of the battery configuration of the $\text{S@C/MXene} \text{LMO}$ cell; b) The charge/discharge profiles of the Li-SI batteries with/without interlayer at the current density of 0.2 C; c) the cycling performance of the batteries with/without MXene interlayer at the current density of 0.5 C.	163
Figure 6.8. The EIS spectra of the batteries with/without MXene interlayer, the inset shows the simulated equivalent circuit.....	165

ABSTRACT

Recently, tremendous efforts have been devoted to the development of novel materials for advanced energy storage devices that simultaneously possess high energy density and power density. Two-dimensional (2D) materials have been considered to be promising in the field of large-scale energy storage. After the discovery of graphene, a large family of two-dimensional transition metal carbides/nitrides (MXenes), derived from MAX phase precursors, have attracted extensive attention owing to the superior physical and chemical properties, which includes excellent electrical conductivity, high mechanical strength, hydrophilic features, multiple possible surface functional groups, superior specific surface area, and the ability to accommodate intercalants. In this thesis, the preparation strategies, structures, properties, and applications of MXene materials in lithium-based and potassium-based batteries have been systematically reviewed. Moreover, we rationally design various MXene materials for lithium-iodine, potassium metal, and aqueous lithium-sulfur batteries. The usage of MXene materials can effectively enhance the electrochemical performances of these energy storage devices. This thesis may provide an insight into the development of two-dimensional MXene materials for large-scale energy storage.